



**PETRONAS**

## TECHNICAL CHARACTERISTICS

**SELENIA StAR**

**PRODUCT CODE: 1138**

### APPLICATION

HIGH PERFORMANCE synthetic lubricant designed to protect ALFA ROMEO gasoline engines in very severe condition generated by a sporty driving style.

### SPECIFICATIONS

SAE 5W-40, ACEA A3/B4, API SM,  
FIAT 9.55535-H2 CONTRACTUAL TECHNICAL REFERENCE N°F216.D05, GM-LL-B-025 Performance,  
VW 502 00/505 00 Performance, RENAULT RN700/RN710 Performance, PORSCHE A40 Performance,  
BMW LL-01 Performance, MB 229.3 Performance

### TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	B. & C.
DENSITY AT 15°C	ASTM D4052	g/cm <sup>3</sup>	0,856
VISCOSITY AT 100°C	ASTM D445	cSt	15,0
VISCOSITY INDEX	ASTM D2270	--	175
T.B.N.	ASTM D2896	mg KOH/g	10,2
FLASH POINT CI. O. C.	ASTM D92	°C	>200
POUR POINT	ASTM D97	°C	<-33
FOAM AT 24°C	ASTM D892	cc/s	TRACES/0

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

03/2017