



PETRONAS

TECHNICAL CHARACTERISTICS

SELENIA K

PRODUCT CODE: 1142

APPLICATION

Synthetic lubricant ideal for the most modern petrol engines. Owing to its unique formula, it warrants high resistance to oxidation, the utmost protection in "Stop & Go" driving and outstanding performance whatever the weather.

SPECIFICATIONS

SAE 5W-40, ACEA A3/B4, API SN/CF, FCA 9.55535-M2 C.T.R.N°F214.I05, BMW LL-01, MB-Approval 229.5, PORSCHE A40, RENAULT RN0700/RN0710, VW 502.00-505.00

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	B. & C.
DENSITY AT 15°C	ASTM D4052	g/cm ³	0,856
VISCOSITY AT 100°C	ASTM D445	cSt	15,0
VISCOSITY INDEX	ASTM D2270	--	175
FLASH POINT Cl. O. C.	ASTM D92	°C	>200
T.B.N.	ASTM D2896	mg KOH/g	10,2
POUR POINT	ASTM D97	°C	<-33
FOAM AT 24°C	ASTM D892	cc/s	TRACES/0

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

05/2018