



PETRONAS

TECHNICAL CHARACTERISTICS

SELENIA MULTIPOWER C3

PRODUCT CODE: 1157

APPLICATION

High performance synthetic lubricant formulated for latest generation of petrol and Diesel engines. Specifically for engines fitted with particulate filter, it warrants outstanding fuel economy.

SPECIFICATIONS

SAE 5W-30, ACEA C3, API SM/CF, BMW LL-04 Performance, MB 229.51 Performance, VW 502 00/505 00/505 01 Performance, FIAT 9.55535-S3 CONTRACTUAL TECHNICAL REFERENCE N°F129.F11, MS-11106

TEST DESCRIPTION

TEST DESCRIPTION	METHOD	UNIT	TYPICAL VALUE
APPEARANCE	--	--	B. & C.
DENSITY AT 15°C	ASTM D4052	g/cm ³	0,850
VISCOSITY AT 100°C	ASTM D445	cSt	11,7
VISCOSITY INDEX	ASTM D2270	--	165
FLASH POINT CI. O. C.	ASTM D92	°C	> 200
T.B.N.	ASTM D2896	mg KOH/g	7,1
POUR POINT	ASTM D97	°C	<-33
FOAM AT 24°C	ASTM D892	cc/s	TRACES/0

All technical data is provided for reference only.

RESEARCH & DEVELOPMENT

05/2016